



# AUI FB7000 Series

## EXTREMELY HIGH-SPEED 24-PIN FLATBED IMPACT PRINTER

- Print up to 528 CPS
- 1+6 multipart forms capability
- Stable and reliable paper handling
- Compatible with various paper form
- USB and Parallel ports
- Optional Ethernet or Bluetooth ports

*\*Formerly known as Seikosha/Seiko Precision Corp. Inc.*

SPECIFICATIONS	FB-7800	FB-7600	
Print Method	24-pin dot matrix impact, bi-directional with logic seeking		
Print Width	136 columns	82 columns	
Print Speed	10 CPI	12 CPI	15 CPI
	High speed draft : 440 cps	528 cps	660 cps
	Draft : 383 cps	460 cps	575 cps
	Normal : 192 cps	230 cps	288 cps
LQ : 128 cps	154 cps	192 cps	
Line Feed Speed	8 inch/second (Fanfold paper) / 21 ms/line (1/6 inch)		
Emulation	EPSON ESC/P, IBM 2391		
Data Buffer	256 Kbytes		
Resident Fonts	Roman, Sans-serif, Courier, Prestige, Script, OCR-A, OCR-B and Orator		
Character Set	17 International character sets / 29 code pages		
Barcode	EAN-13, EAN-8, Interleaved 2 of 5, Matrix 2 of 5, Industrial 2 of 5, Code 39, Code 128B, Code 128C, and Codabar		
Paper Feed	Push tractor or friction		
Paper Path	Fanfold : Rear in-Front out		
	Cut sheet : Front Manual Insertion, front or rear ejection is selectable.		
	Detection function : Paper skew detection, Paper edge detection, Black mark detection, Paper loading at any position, Paper thickness detection, Copy capacity auto adjustment		
Paper Width	Fanfold : 101.6 – 430 mm	Fanfold : 60 – 280 mm	
	Cut sheet : 75 – 440 mm	Cut sheet : 55 – 297 mm	
	Passbook/Certificate : 90 – 400 mm	Passbook/Certificate : 90 – 297 mm	
Paper Length	Cut sheet : 67 – 536 mm	Cut sheet : 67 – 536 mm	
	Passbook/Certificate : 75 – 400 mm	Passbook/Certificate : 75 – 300 mm	
	Thickness < 1.5mm	Thickness < 1.5mm	
Paper Thickness	2.0 mm max.		
Multipart Forms	Original plus 6 duplicates		
Ribbon Life	14 million characters (Draft mode)	10 million characters (Draft mode)	
Printing Model	#FB-70051	#FB-70001	
Interface	Standard : Parallel (Bidirectional / IEEE 1284), USB (2.0 Full Speed)		
	Options : Ethernet (10/100 Base-T), Bluetooth, Wi-Fi (802.11b/g/n) (* note: Choose 1 additional interface from these 3 options)		
Printhead Life	300 million strokes/wire		
MTBF	20,000 hours		
Noise	59dB(A) (ISO7779 standard)		
Power Supply	Rated voltage : AC220-240V		
	Rated frequency range : 50 Hz		
Power Consumption	Operation : 90 watts	Operation : 110 watts	
	Standby : 2.5 watts	Standby : 3.4 watts	
Dimensions	580(W) mm x 246(D) mm x 210(H) mm	422(W) mm x 239(D) mm x 200(H) mm	
Weight	Approx. 8.15 kg	Approx. 5.2 kg	