



# AUI FB600E

## 24-PIN WIDE-CARRIAGE DOT MATRIX PRINTER

- User-Friendly Interface
- Stable and Reliable Paper Handling
- Enhanced Interfaces (Parallel, USB & Ethernet)
- Automatic Sheet Alignment Function
- Maximum 2.0 mm Thickness Capability
- Printable on Variety of Media

*\*Formerly known as Seikosha/Seiko Precision Corp. Inc.*

### SPECIFICATIONS

Print method	24-pin dot matrix impact, bi-directional (text & graphics)
Print speed	Super speed draft (SSD 15 cpi) : 600 cps Speed draft (SD 12 cpi) : 480 cps Draft (10 cpi) : 400 cps
Line feed speed	36 lines/second
Emulation	EPSON LQ-2550, IBM 2391
Data buffer	132 Kbytes
Resident fonts	Roman, Sans-serif, Courier, Prestige, Script, OCR-A, OCR-B and Orator
Character Set	ASCII: 17 International character sets
Barcode	Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5 Code 39, Code 128B, Code 128C, EAN-8, EAN-13 and NW-7
Paper feed	Push tractor or friction
Paper path	Fanfold : Front push tractor (*1) : Rear push tractor (*1) Cut sheet : Front Manual Insertion, front or rear ejection is selectable. Detection function : Paper Jam, Paper Skew, Paper Width (Left and Right Edge)
Paper width	Fanfold : 203.2 – 381 mm Cut sheet : 182 – 430 mm (manual) : 182 – 420 mm (CSF)
Paper thickness	Fanfold : 0.52 mm max. Cut sheet : 2.0 mm max. (manual) Cut sheet : 0.12 mm max. (CSF)
Multipart forms	Original plus 6 duplicates (Dark mode) Original plus 4 duplicates (Normal mode)
Operating panel	Graphic LCD, Paper path lever, Gap adjust lever (*2)
Printing ribbon	Special cassette-type black fabric ribbon Ribbon life: 15 million characters (Draft mode)
Interface	Parallel (Bidirectional / IEEE 1284), USB (2.0 Full Speed), Ethernet (10/100 Base-T) Option: RS-232C (DB-9 pin or DP-25 pin)
Printhead life	300 million characters (Draft mode)
MTBF	10,000 hours
Power supply	AC230V model or AC120V model
Power consumption	110 watts (operation) 16.5 watts (standby) 14 watts (sleeping mode)
Dimensions	635(W) x 465(D) x 294(H) mm at Operation 635(W) x 335(D) x 294(H) mm at Storage
Weight	Approx. 22.0 kg

\*1. Removable tractor unit can be used front and rear.

\*2. The paper path and gap are automatically adjusted according to the lever setting position.