



AUI FB630

24-PIN WIDE-CARRIAGE DOT MATRIX PRINTER

High-speed flatbed printer compatible with multi paper form and catering to various needs

- Enhanced print head for higher speed
- User friendly interface
- Stable and reliable paper handling
- Automatic sheet alignment function
- Compatible with various paper form
- Maximum 2.0mm thickness capability

**Formerly known as Seikosha/Seiko Precision Corp. Inc.*

SPECIFICATIONS

Print Method	24-pin dot matrix impact, bi-directional (text & graphics)
Print Speed	Super speed draft (SSD 15 cpi) : 600 cps Speed draft (SD 12 cpi) : 528 cps Draft (10 cpi) : 440 cps HQDR (10 cpi) : 360 cps NLQ (10 cpi) : 240 cps LQ (10 cpi) : 180 cps
Line Feed Speed	70 lines/second
Emulation	EPSON LQ-2550, IBM 2391
Data Buffer	132 Kbytes
Resident Fonts	Roman, Sans-serif, Courier, Prestige, Script, OCR-A, OCR-B and Orator
Character Set	ASCII: 17 International character sets
Barcode	Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5 Code 39, Code 128B, Code 128C, EAN-8, EAN-13 and NW-7
Paper Feed	Push tractor or friction
Paper Path	Fanfold : Front push tractor (*1) : Rear push tractor (*1) Cut sheet : Front Manual Insertion, front or rear ejection is selectable. Detection function : Paper Jam, Paper Skew, Paper Width (Left and Right Edge)
Paper Width	Fanfold : 127 – 406 mm Cut sheet : 127 – 430 mm
Paper Thickness	Fanfold : 0.52 mm max. Cut sheet : 2.0 mm max.
Multipart Forms	Original plus 6 duplicates (Dark mode) Original plus 4 duplicates (Normal mode)
Operating Panel	Graphic LCD, Paper path lever, Gap adjust lever (*2)
Printing Ribbon	Special cassette-type black fabric ribbon Ribbon life: 15 million characters (Draft mode)
Interface	Parallel (Bidirectional / IEEE 1284), USB (2.0 Full Speed) Ethernet (10/100 Base-T) - optional Options: RS-232C (DB-9 pin or DP-25 pin)
Printhead Life	300 million characters (Draft mode)
MTBF	20,000 hours
Power Supply	AC100-240V
Power Consumption	110 watts (operation) 4.9 watts (standby)
Dimensions	635(W) x 465(D) x 294(H) mm at Operation 635(W) x 335(D) x 294(H) mm at Storage
Weight	Approx. 22.0 kg

*1. Removable tractor unit can be used front and rear.

*2. The paper path and gap are automatically adjusted according to the lever setting position.