

Olivetti PR2 PLUS

SPECIALISED PRINTER



- Among The Smallest & Quietest In Its Product Class
- Extremely Easy To Use
- Management Of All Bank Forms
- Ultra-Fast Alignment For Improved Performance
- Magnetic-Stripe Reading & Writing, MICR Codeline Reading (CMC7 / E13B)
- Outstanding Graphics Management
- Superior Printing Speed: Up To 560 Char/Sec In VHSD
- New Ink Ribbon Prints Up To 10 Million Characters

SPECIFICATIONS

Technology	24-pin dot matrix
Resolution	240 x 360 dpi
Fonts	OCR A-B, ROMAN, Sans Serif, Italic, Courier
Pitch	10, 12, 15, 16.6, 17.1 cpi
Printing speed at 10 cpi	VHSD: 560 cps HSD: 510 cps Draft: 370 cps NLQ: 185 cps
Line length	238.76 mm (94 columns at 10 cpi)
Line spacing	1/5", 1/6", n/216", n/240"
Copies	Original + 6 copies
Interfaces	Standard: RS232 serial, IEEE 1284 parallel and USB 2.0
Emulations	Olivetti Standard, IBM PP & X24 Optional: IBM 4722/9068, IBM PP & X24, WINCOR 4915, EPSON LQ 2550, UNISYS EFP series
Noise level	< 54 dBA (ISO 7779 with ECMA 132 text)
Document handling	Feed width: 245 mm Completely flat paper feed Automatic insertion with autoborder Automatic document-thickness monitoring
Power consumption	Min. 6.5 W (9 W in scanner model) Max. 85 W (printing)
Ribbon cartridge	10 million characters
Voltage	230V / 50Hz 115V / 60Hz
Certifications & Regulatory	CE, TÜV NRTL, FCC class A verified
Options	MICR reader (CMC7, E13B) Scanner
Dimensions	384(W) x 296(D) x 204(H) mm (15.12" x 11.65" x 8.03")
Weight	10.5 Kg