



# ABS P600

## POS THERMAL PRINTER

- Compatible with EPSON ESC/POS and STAR Command Sets
- Built-in Web Page for Direct Printer Set Up and Printer Status Monitoring
- Supports Connection for WAN Printing
- 250mm/sec Ultra High Speed Printing
- Windows X86 / X64 / Linux / OPOS Driver
- Faster Connection and Printing to Prevent Misprinting of Receipt

### SPECIFICATIONS

Print method	Direct thermal line
Print width	64/72 mm
Print speed	250 mm/s
Dot density	512/576 dot/line
Paper diameter	83 mm
Line space	3.75 mm (adjustable)
Auto function	Paper end and black mark detection
Interface	Serial + USB + Ethernet; Parallel + USB port Virtual serial port mode-USB port supports OPOS application
Language	Supports up to 68 international languages
Character size	ANK Font A: 12 x 24 dots Font B: 9 x 17 dots Simplified/Traditional chinese characters: 24 x 24 dots
Barcode mode	UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) CODE39 / ITF / CODABAR / CODE93 / CODE128
Barcode fonts	GB18030
Buffer data	128 Kbytes
Buffer NV Flash	256 Kbytes
Power	Cashdrawer out: DC 24 V / 1A Power supply: AC 110V / 220V, 50-60 Hz, DC 24V / 2A
Environment	Work: Temperature: 0-45°C Humidity: 10-80% Storage: Temperature: -10-60°C Humidity: 10-90%
Auto cutter reliability	150 km
Dimensions	145(W) x 210(D) x 140(H) mm
Weight	1.4 kg