



QDK TP850

HIGH-SPEED & HIGH PERFORMANCE THERMAL RECEIPT PRINTER

- Paper Width: 80 mm
- Fast Printing Speed: 300 mm/second
- Better Connectivity With
Serial + USB / Ethernet + USB /
Parallel / USB / Bluetooth + USB /
Wi-Fi + USB Interface
- Auto Cutter

SPECIFICATIONS

Print method	Thermal line printing												
Print width	72 mm / 576 dots (paper width: 79.5 ± 0.5 mm)												
Print speed	300 mm/sec												
Resolution	203 x 203 dpi (maximum)												
Bar code	UPC-A, UPC-E, EAN-13, EAN-8, Code39, Code128, ITF-25, Codabar												
Line space	30/203 inch, programmable in 1/203 inch increments												
Emulation	EPSON ESC/POS												
Interface Options	Parallel, USB 2.0, Serial + USB 2.0, Ethernet + USB 2.0, Bluetooth + USB 2.0, Wifi + USB 2.0												
Input buffer	4MB												
Noise	< 38 dB (A) (ISO7779 standard)												
Paper feed type	Feed paper by friction Weight: 53 – 80 g/m ² Roll diameter: 83mm (maximum)												
Max paper thickness	0.065 – 0.12 mm												
Function	Online parameter setting / Auto cutter												
Power requirement	<table border="0"> <tr> <td>Input</td> <td>Rated voltage:</td> <td>100 – 240V</td> </tr> <tr> <td></td> <td>Rated frequency range:</td> <td>50 – 60Hz</td> </tr> <tr> <td>Output</td> <td>Rated voltage:</td> <td>DC 24V</td> </tr> <tr> <td></td> <td>Rated current:</td> <td>2.5A</td> </tr> </table>	Input	Rated voltage:	100 – 240V		Rated frequency range:	50 – 60Hz	Output	Rated voltage:	DC 24V		Rated current:	2.5A
Input	Rated voltage:	100 – 240V											
	Rated frequency range:	50 – 60Hz											
Output	Rated voltage:	DC 24V											
	Rated current:	2.5A											
Dimension	148(W) x 207(D) x 135(H) mm												
Weight	Approx. 1.45 kg												